

C & R TESTING LTD

Compressed Air Filters

Aydın Trafo air dryer filters are equipped with automatic water drain system and gauge type indicator which indicates the changing time of inner filter element.



Compressed Air Filters

Type	Capacity (m³/dak)			Max. Working Pressure (bar)
	7 bar	10 bar	13 bar	
TMP HF-25	0,42	0,35	0,32	16
TMP HF-50	0,83	0,69	0,63	16
TMP HF-100	1,66	1,38	1,26	16
TMP HF-150	2,50	2,08	1,89	16
TMP HF-200	3,33	2,78	2,52	16
TMP HF-250	4,16	3,47	3,15	16
TMP HF-300	5,0	4,17	3,79	16
TMP HF-500	8,33	6,94	6,31	16
TMP HF-600	10,0	8,33	7,58	16
TMP HF-851	14,18	11,82	10,74	16
TMP HF-1210	20,16	16,80	15,27	16
TMP HF-1510	25,16	20,97	19,06	12
TMP HF-1810	30,16	25,13	22,85	12
TMP HF-2210	36,83	30,69	27,90	12
TMP HF-2496	41,60	34,67	31,52	12
TMP HF-3198	53,30	44,42	40,38	12

C & R Testing Ltd.
 Unit 1 Owenshaw Mills, Old Cawsey, Sowerby Bridge, Halifax.
 HX6 2AF
 Tel: +44 (0)1422 410466, Email: info@candrtesting.co.uk