W31 VERTICAL



Standard Features

- P21 Purifier with Refillable Purifier Element
- 2nd and 3rd Stage Water Condensate & Oil Seperator
- Intercoolers (Stainless Steel)
- Aftercooler (Stainless Steel)
- Priority Valve (Pressure Maintaining Valve)
- Check Valve
- Safety Valve at Each Stage
- Oil Level Sight Gauge
- Shock Mounts
- Electrostatically Painted Portable Chassis
- Manual Start / Stop
- Manual Condensate Drain
- Power Cable & Plug
- Thermal Overload Protection for Electric Motor
- Control Panel: On / Off Buttons & Hourmeter
- 1* Filling Hose (Yokes, Filling Valves, Pressure Gauges, DIN Adapters)
- Breathing Air Quality Complies with EN 12021

Optional Features

- Automatic Start / Stop
- Automatic Condensate Drain
- Pressure Switch
- Dual Pressure System 225-310 Bar / 3260-4500 Psi
- Stainless Chassis
- Extra Filling Hoses
- Disposable Filter Cartridge

Sectors

- Scuba Diving
- Fire Departments
- Military Applications
- Naval Applications
- Civil Defense Applications
- Gas Filling Facilities
- Maritime Applications
- Industrial Applications
- Fish Farms
- Paintball

Model	Working Pressure		Free Air Delivery (FAD)*			Motor Power		Speed (rpm)	Number of Stage	Weight	Dimensions (cm)		ons
	bar	psi	lt/min	m ³ /h	cfm	Нр	kW			kg	W	L	Н
W31	225/310	3260/4500	105	6,3	3,7	3	2,2	1050	3	67	59	50	88
Vertical	225/310	3260/4500	140	8,4	4,9	4	3	1350	3	67	59	50	88

*Based on recharging a 10 It cylinder from 0 to 200 barg.

**Higher pressure models up to 350 Bar are available.

***ALKIN COMPRESSOR can change information and pistures in their brochure without any prior notice.