

C & R TESTING LTD

ALKIN High Pressure Compressors » W4 BASE MOUNTED

Standard Features

- P61 Purifier (stainless steel) with Refillable Purifier Element (stainless steel)
- High Pressure Particle and Oil Removal Filter (Stainless Steel)
- 2nd and 3rd stages Water Separator (Stainless Steel)
- Inter coolers
- After cooler (Stainless Steel)
- Priority Valve (Pressure Maintaining Valve)
- Check Valve
- Removable Filling Panel with 4 Filling Hoses (Yokes, Filling Valves) and Cylinder Pressure Gauge
- Auto Drain
- Automatic Start/Stop
- Oil Level Switch
- Control Panel: 4 Stage Pressure Gauges, Main Switch, On/Off Buttons, Hour meter, Test, Reset and Emergency Push buttons , 5 Control Leads
- Tropical Cooling with Electric Ventilation Fans
- Air Quality comply with EN 12021



Optional Features

- Extra Filling Hoses
- Dual Pressure Systems (225-310 Bar/3260-4500 Psi)
- Disposable Filter Cartridge
- Electronic Control System

Sectors

- Scuba Diving
- Fire Brigades
- Military Applications
- Naval Applications
- Fish Farms
- Gas Filling Facilities
- Marine

ALKIN Model	Working Pressure		Displacement Capacity		Motor Power		RPM	No of stage	No of cylinders	Weight	Dimensions(cm)		
	Bar	Psi	Lt/min	Cfm	Hp	Kw					Width	Length	Height
W4 Base Mounted	225	3260	394	13.9	10	7.5	640	4	3	730	84	168	143.5
	310	4500	375	13.2	10	7.5	640	4	3	730	84	168	143.5
	225	3260	557	19.7	15	11	840	4	3	740	84	168	143.5
	310	4500	528	18.7	15	11	840	4	3	740	84	168	143.5
	225	3602	625	22.1	20	15	950	4	3	780	84	168	143.5
	310	4500	594	21	20	15	950	4	3	780	84	168	143.5
	415	6025	550	22	20	15	950	4	3	780	84	168	143.5

Higher pressure models up to 350 Bar are available

ALKIN COMPRESSOR can change information and pictures in their brochure without any prior notice.

C & R Testing Ltd.
Unit 1 Owenshaw Mills, Old Cawsey, Sowerby Bridge, Halifax.
HX6 2AF
Tel: +44 (0)1422 410466, Email: info@candrtesting.co.uk